



Digital Camera 10.1 Megapixels DCC-1025



Superior image clarity (10.1 Megapixels) and a large 2.5" LCD Display

Product Features

- 10.1 Megapixel Digital Camera
- Captures high-resolution images up to 3648 x 2736
- 2.5" LTPS TFT LCD, scratch-resistant acrylic panel display
- 3x optical zoom and 4x digital zoom
- Movie mode captures video clips with resolutions of 640 x 480, 320 x 240, and 160 x 120
- Built-in flash with auto, red-eye reduction, always on, slow sync, forced on, forced off
- Manual, daylight, cloudy, tungsten, fluorescent and custom white balance settings
- 15 picture taking modes: Program, movie, voice REC, portrait, landscape, sunset, night scene, text, back light, kids, snow, food, fireworks, building, quickmode (English only)

Preliminary & Confidential

Norcent

Digital Camera 10.1 Megapixels DCC-1025

Product Specifications

Special Features

| • | | |
|---------------------|---|--|
| Number of Pixels | I | 10.1 Mega Pixels |
| Image Resolution | I | 3648x2736(10M), 3648x2432(3:2), 3264x2448(8M), |
| | | 2560x1920(5M), 2048x1536(3M),640x480 |
| File Formats | I | Still: EXIF 2.2 compatible format, (JPEG compression) |
| | | DCF compatible, Supports DPOF |
| | | Video: AVI, MPEG-4 w/audio |
| | | Audio:WAV |
| Imaging Elements | I | 2.5"Type, 28-pin Plastic SOP |
| Lens | I | Focal length: f=7.94 (W) - 22.71 (T)mm, (35mm film |
| | | equivalent: 38.01-108.73) |
| LCD Display | I | 2.5" LTPS TFT color LCD |
| Zoom | I | 3x optical zoom, 4x digital zoom |
| Focus Range | I | Normal: (W) 80cm - Infinity (from the tip of barrier) |
| | | Macro: (W) 5cm - 80cm / (T) 25cm - 80cm |
| Exposure Meter | I | Center-weighted, multi, spot |
| Exposure Control | I | Default Auto, Exposure compensation: -2EV to |
| | | +2EV in 1/3 step |
| Shutter Speed | I | Mechanical Shutter, shutter speed:1/2000~ 8 sec. with |
| | | CCD variable electronic shutter |
| Aperture | I | F/2.8 (W), 5.1(T) |
| White Balance | I | Manual(6 modes in manual selection: daylight, cloudy, |
| | | tungsten, fluorescent (H), fluorecent (L), customer) |
| Scene Modes | I | 15 modes: Program, movie, voice REC, portrait, landscape, |
| | | sunset, night scene, text, back light, kids, snow, food, |
| | | fireworks, building, quickmode (English only) |
| Sensitivity | I | Default Auto, Auto, ISO 50, ISO 100, ISO 200 |
| Self-Timer | I | 10 sec, 2 sec, single shot and Double self-timer |
| Built-in Flash | I | 5 modes: Default Auto, Auto, Red-eye reduction, Always on, |
| | | Slow sync, Forced On, Forced Off |
| Photo effects | I | Off, Black & White, Sepia, Negative Art, Mosaic |
| Burst | I | Contiunous, unlimited |
| Recording Functions | I | Resolution: 640x480 / 320x240 / 160x120 (@30fps) |
| | | Recording time: until media is full |
| Voice Memo | I | Max 30 sec. along with an image file (still & movie) |
| TV System | I | NTSC/PAL (selected by MENU) |
| Storage | I | 32MB internal memory, SD/MMC card slot |
| Languages | I | English, German, French, Japanese, Italian, Korean, |
| | | Spanish, Simplified Chinese, Traditional Chinese, Dutch, |
| | | Russian, Portuguese, Czech, Polish, Turkish, Hungarian |
| Power Supply | I | AA battery x2: 110 shots (with new alkaline battery), or |
| | | rechargeable |
| | | Ni-MH battery x2 (not included) |
| Dimensions | I | (W) 3.5"x(H) 2.4"x(D) 1.1" (max 1.05" Lens - LCD) |
| Unit Weight | I | .3 lbs. |
| Accessories | I | USB Cable, AV Cable, Wrist Strap, Camera Bag, |
| | | User Manual, Software CD |
| | | |

UPC# 803802352069

Norcent is a registered trademark of Norcent Technology Inc. (2005) 550 Cliffside Drive, San Dimas, CA 91773 All rights reserved. All product information is accurate to the best of our knowledge at the time of publication.

All product information is accurate to the best of our knowledge at the time of publication. Features and specifications are subject to change without notice.





